

# REMS RAS St

## Pipe cutters

Robust quality tools for cutting pipes.  
Meets high demands and long service life.

Steel pipes  $\varnothing$  1/8–4",  $\varnothing$  10–115 mm

REMS cutter wheels for other makes see page 74.

### REMS RAS St – quality pipe cutters.

Solid body in forged steel.

Robust spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe and a long service life.

Ergonomic, wide handle provides a powerful in-feed of spindle.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for pipes  $\varnothing$  1/8–4" (10–115 mm), wall thickness  $s \leq 8$  mm, suitable for both pipe cutters. Cutter wheel for pipes  $\varnothing$  1–4" to wall thickness  $s \leq 12.5$  mm available as accessory.



German Quality Products

### Supply format

**REMS RAS St.** Pipe cutter for steel pipes. With cutter wheel. In cardboard box.

Description	Pipes $\varnothing$ mm/inch	Wall thickness $s \leq$ mm	Art.-No.
St 1/8–2"	1/8–2" 10–60	8	113000
St 1 1/4–4"	1 1/4–4" 30–115	8	113100

### Accessories

Description	$s \leq$ mm	Art.-No.
<b>REMS cutter wheel St 1/8–4", s 8</b> for REMS RAS St 1/8–2" and St 1 1/4–4"	8	341614
<b>REMS cutter wheel St 1–4", s 12</b> for REMS RAS St 1 1/4–4"	12.5	381622



# REMS RAS Cu-INOX

## Tubing cutters

Robust quality tools for cutting tubes.  
Particularly suited for cutting stainless steel tubes.

Copper tubes, thin-walled  
stainless steel tubes, thin-walled  
steel, aluminium, brass tubes  $\varnothing$  3–120 mm  
 $\varnothing$  1/8–4"

REMS cutter wheels for other makes see page 74.

**REMS RAS Cu-INOX** for tubes  $\varnothing$  3–16 mm, 1/8–5/8"  
**REMS RAS Cu-INOX Mini** for tubes  $\varnothing$  3–28 mm, 1/8–1 1/8"

Small, handy, specially for use in restricted spaces.

Robust design and hardened back pressure rollers provide exact alignment to the tube and a long service life.

Large operating knob in metal for easy in-feed and cutting.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.



### Supply format

**REMS RAS Cu-INOX.** Tubing cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel.

In pressure-sealed plastic bag.

Description	Pipes $\varnothing$ mm/inch	Wall thickness $s \leq$ mm	Art.-No.
<b>Cu-INOX 3–16</b>	3–16 1/8–5/8"	4	113200
<b>Cu-INOX 3–28 Mini</b>	3–28 1/8–1 1/8"	4	113240



# REMS RAS Cu-INOX

Tubing cutters

## REMS RAS Cu-INOX for tubes Ø 3–35 mm, 1/8–1 3/8" REMS RAS Cu-INOX for tubes Ø 3–42 mm, 1/8–1 3/4"

Telescopic spindle. Easy, quick adjustment in both directions.

Compact design for tough use.

Sturdy telescopic spindle, long spindle guidance and 4 specially hardened back pressure rollers ensure exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Integrated pipe deburring device, on rotating bearing, adapts to the workpiece edge to be deburred.

Specially hardened and ground universal deburring blade guarantees easy deburring and extremely long life.

Fast, simple blade change.



### Supply format

**REMS RAS Cu-INOX.** Pipe cutting machine for copper pipes, thin-walled stainless steel pipes, thin-walled steel-aluminium pipes, brass pipes, with integrated pipe deburring device. With cutter wheel. In pressure-sealed plastic bag.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.
<b>Cu-INOX 3–35</b>	3–35 1/8–1 3/8"	4	113350
<b>Cu-INOX 3–42</b>	3–42 1/8–1 3/4"	4	113330



## REMS RAS Cu-INOX for tubes Ø 3–28 mm, 1/8–1 1/8" REMS RAS Cu-INOX for tubes Ø 6–42 mm, 1/4–1 5/8" REMS RAS Cu-INOX for tubes Ø 6–64 mm, 1/4–2 1/2" REMS RAS Cu-INOX for tubes Ø 64–120 mm, 2 1/2–4"

Robust, solid design for heavy-duty application.

Sturdy spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the tube, easy in-feed, easy cutting and precise, right angle cut.

Ergonomic, handy operating knob in metal for easy work and long service life.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for the complete working capacity Ø 3–120 mm.



International  
Design Award



German Quality Products

### Supply format

**REMS RAS Cu-INOX.** Tubing cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel. In pressure-sealed plastic bag / cardboard box.

Description	Pipes Ø mm/inch	Wall thickness s ≤ mm	Art.-No.
<b>Cu-INOX 3–28</b>	3–28 1/8–1 1/8"	4	113300
<b>Cu-INOX 6–42</b>	6–42 1/4–1 5/8"	4	113380
<b>Cu-INOX 6–64</b>	6–64 1/4–2 1/2"	4	113400
<b>Cu-INOX 64–120</b>	64–120 2 1/2–4"	4	113500

### Accessories

Description	Wall thickness s ≤ mm	Art.-No.
<b>REMS cutter wheel Cu-INOX 3–120, s 4</b>	4	113210
<b>Universal deburring blade, ground</b>		113360

