


Accessoires de réseaux

Piquages express PS à 90°

Dimensions (mm)		Galva standard		Galva avec joints	
Ø D	Ø d	REF	CODE	REF	CODE
450	450	PS 450/450	543 311	PS 450/450 J	530 034
450	500	PS 450/500	543 037	PS 450/500 J	530 035
450	560	PS 450/560	543 312	PS 450/560 J	530 036
450	630	PS 450/630	543 313	PS 450/630 J	530 037
450	710	PS 450/710	543 360	-	-
450	800	PS 450/800	543 435	-	-
500	500	PS 500/500	533 654	PS 500/500 J	530 038
500	560	PS 500/560	543 314	PS 500/560 J	530 039
500	630	PS 500/630	543 036	PS 500/630 J	530 040
500	710	PS 500/710	533 035	-	-
500	800	PS 500/800	543 535	-	-
560	560	PS 560/560	543 315	-	-
560	630	PS 560/630	523 203	-	-
560	710	PS 560/710	533 237	-	-
560	800	PS 560/800	543 026	-	-
630	630	PS 630/630	543 316	-	-
630	710	PS 630/710	533 036	-	-
630	800	PS 630/800	543 401	-	-

Piquages express PS à 45°

Dimensions (mm)		Galva standard	
Ø D	Ø d	REF	CODE
125	125	PS 125/125-45	543 786
125	160	PS 125/160-45	543 683
125	200	PS 125/200-45	543 684
125	250	PS 125/250-45	543 685
125	315	PS 125/315-45	533 706
125	355	PS 125/355-45	543 514
125	400	PS 125/400-45	524 801
160	160	PS 160/160-45	543 847
160	200	PS 160/200-45	543 860
160	250	PS 160/250-45	543 849
160	315	PS 160/315-45	543 478
160	355	PS 160/355-45	543 431
160	400	PS 160/400-45	543 479
200	200	PS 200/200-45	543 520
200	250	PS 200/250-45	533 707
200	315	PS 200/315-45	547 111
200	355	PS 200/355-45	543 432
200	400	PS 200/400-45	533 705
200	500	PS 200/500-45	543 715
200	630	PS 200/630-45	547 106
250	250	PS 250/250-45	543 447
250	315	PS 250/315-45	543 743
250	355	PS 250/355-45	543 513
250	400	PS 250/400-45	543 511
250	500	PS 250/500-45	547 148
250	630	PS 250/630-45	533 243
315	315	PS 315/315-45	547 116
315	355	PS 315/355-45	543 433
315	400	PS 315/400-45	543 744
315	500	PS 315/500-45	543 522
315	630	PS 315/630-45	543 521
355	355	PS 355/355-45	547 174
355	400	PS 355/400-45	543 524
355	500	PS 355/500-45	543 527
355	630	PS 355/630-45	547 149
400	400	PS 400/400-45	533 244
400	450	PS 400/450-45	533 245
400	500	PS 400/500-45	543 426
400	560	PS 400/560-45	543 518
400	630	PS 400/630-45	543 592
450	450	PS 450/450-45	547 176
450	500	PS 450/500-45	533 246
450	560	PS 450/560-45	547 140
450	630	PS 450/630-45	547 128



Piquages plats à 90°

Dimensions (mm)		Galva standard	
Ø D		REF	CODE
80		PP 80	533 579
100		PP 100	533 577
125		PP 125	523 281
160		PP 160	523 282
200		PP 200	523 283
250		PP 250	523 284
315		PP 315	523 285
355		PP 355	533 145
400		PP 400	533 575
450		PP 450	524 100
500		PP 500	523 984
560		PP 560	543 048
630		PP 630	533 576
710		PP 710	524 098
800		PP 800	524 099

Piquages plats à 45°

Dimensions (mm)		Galva standard	
Ø D		REF	CODE
80		PP 80-45	544 903
100		PP 100-45	543 716
125		PP 125-45	533 582
160		PP 160-45	533 583
200		PP 200-45	533 581
250		PP 250-45	533 578
315		PP 315-45	533 708
355		PP 355-45	533 580
400		PP 400-45	547 150
450		PP 450-45	533 398
500		PP 500-45	547 146