


Coude à secteurs (> Ø 200)



Coude embouti (≤ Ø 200)



Coude avec joints



Coude à 45° et 30°



Coudes à 90°

Dimensions (mm)	Galva standard		Galva avec joints		Aluminium standard	
	REF	CODE	REF	CODE	REF	CODE
Ø D						
80	C 80/90	523 219	C 80/90 J	547 373	-	-
100	C 100/90	523 850	C 100/90 J	529 600	C 100/90 AL	543 207
125	C 125/90	523 521	C 125/90 J	529 601	C 125/90 AL	523 884
160	C 160/90	523 522	C 160/90 J	529 602	C 160/90 AL	523 885
200	C 200/90	523 523	C 200/90 J	529 603	C 200/90 AL	523 886
250	C 250/90	523 524	C 250/90 J	529 604	C 250/90 AL	523 887
315	C 315/90	523 525	C 315/90 J	529 605	C 315/90 AL	523 888
355	C 355/90	523 528	C 355/90 J	529 606	C 355/90 AL	523 747
400	C 400/90	523 526	C 400/90 J	529 607	C 400/90 AL	523 748
450	C 450/90	523 238	C 450/90 J	529 608	C 450/90 AL	524 014
500	C 500/90	523 527	C 500/90 J	529 609	C 500/90 AL	523 749
560	C 560/90	543 101	C 560/90 J	529 069	C 560/90 AL	543 600
630	C 630/90	523 142	C 630/90 J	547 303	C 630/90 AL	533 665
710	C 710/90	523 942	-	-	-	-
800	C 800/90	523 328	-	-	-	-
900	C 900/90	533 113	-	-	-	-

Coudes à 45°

Dimensions (mm)	Galva standard		Galva avec joints		Aluminium standard	
	REF	CODE	REF	CODE	REF	CODE
Ø D						
80	C 80/45	543 171	C 80/45 J	547 600	-	-
100	C 100/45	523 851	C 100/45 J	529 650	C 100/45 AL	543 165
125	C 125/45	523 539	C 125/45 J	529 651	C 125/45 AL	523 892
160	C 160/45	523 533	C 160/45 J	529 652	C 160/45 AL	523 893
200	C 200/45	523 534	C 200/45 J	529 653	C 200/45 AL	523 894
250	C 250/45	523 537	C 250/45 J	529 654	C 250/45 AL	523 895
315	C 315/45	523 538	C 315/45 J	529 655	C 315/45 AL	523 896
355	C 355/45	523 529	C 355/45 J	529 656	C 355/45 AL	523 750
400	C 400/45	523 531	C 400/45 J	529 657	C 400/45 AL	523 751
450	C 450/45	523 237	C 450/45 J	529 658	C 450/45 AL	524 015
500	C 500/45	523 532	C 500/45 J	529 659	C 500/45 AL	523 752
560	C 560/45	543 303	C 560/45 J	529 125	-	-
630	C 630/45	523 143	C 630/45 J	547 304	-	-
710	C 710/45	543 173	-	-	-	-
800	C 800/45	523 329	-	-	-	-

Coudes à 30°

Dimensions (mm)	Galva standard		Galva avec joints	
	REF	CODE	REF	CODE
Ø D				
125	C 125/30	523 692	C 125/30 J	529 122
160	C 160/30	523 693	C 160/30 J	529 121
200	C 200/30	523 694	C 200/30 J	529 120
250	C 250/30	523 695	C 250/30 J	529 119
315	C 315/30	523 696	C 315/30 J	529 100
355	C 355/30	523 697	C 355/30 J	529 118
400	C 400/30	523 698	C 400/30 J	529 117
450	C 450/30	523 707	C 450/30 J	529 116
500	C 500/30	523 699	C 500/30 J	529 113
630	C 630/30	523 619	C 630/30 J	529 114