Start PanelLED
Brilliant LED panels

The new **Start PanelLED** range of recessed LED panels is an ideal solution where a quick, simple and effective upgrade to LED is desired. The range has been designed with corporate offices in mind wether it is in meeting rooms, corridors or back of house applications.

Start PanelLED combines high efficacy LED module and high performance optics to deliver up to 3,950lm (Luminaire lumen output on Neutral white versions) while maintaining high performance with up to 88lm/W.

Additionally, **Start PanelLED** comes with its LED driver and is easy to install thanks to its light weight and Plug and Play connection as standard.

SYLVANIA

Start PanelLED
Brilliant LED panels

FEATURES:

- 45W LED recessed luminaires
- Designed for 600 x 600mm and 625 x 625mm ceiling panels
- Brilliant even distribution of light
- Offers a high light output of up to 3,950lm (luminaire output on 4,000K version)
- Cost effective product - will help you comply with building regulations - up to 88lm/W (total system efficiency)
- Warm white (3,000K) or neutral white (4,000K)
- Slim profile of 86mm for minimal impact into ceiling void, make this an ideal LED upgrade solution
- Quick and easy to install
- Long lifetime - 50,000 hours
- LED technology provides energy efficient solution and reduced maintenance costs

IP20 | 850°C | LED

Start PanelLED

| Item code	Description	Body size (mm)	Body colour	Ballast	Colour name	Colour temperature (K)	Voltage (V)	Drive current (mA)	Power consumption (W)	Luminaire lumen output (lm)	Lumen/ Watt (lm/W)	Life (hours)
Start PanelLED - 600 x 600mm												
0047570	Start PanelLED 600 WW	600 x 600	White	Electronic	Warm white	3,000	220 - 240	1,200	45	3,850	86	50,000
0047571	Start PanelLED 600 NW	600 x 600	White	Electronic	Neutral white	4,000	220 - 240	1,200	45	3,950	88	50,000
Start PanelLED - 625 x 625mm												
0047572	Start PanelLED 625 WW	625 x 625	White	Electronic	Warm white	3,000	220 - 240	1,200	45	3,850	86	50,000
0047573	Start PanelLED 625 NW	625 x 625	White	Electronic	Neutral white	4,000	220 - 240	1,200	45	3,950	88	50,000

Legend: 600 = 600 x 600mm module; 625 = 625 x 625mm module; WW = Warm White; NW = Neutral White

Photometric data

Start PanelLED - 3,000K

Start PanelLED - 4,000K

Dimension (mm)

Start PanelLED - 600 x 600mm

596
596
86

Start PanelLED - 625 x 625mm

620
620
86

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Current details should therefore be checked with Havells Sylvania Europe Limited

SYLVANIA